

GENERAL TIRE

2024 ARCA TIRE SPECIFICATIONS

Speedway Codes (12.0/28.0R15)

Bristol	LS	RS	Charlotte	LS	RS
	1013	2262		1117	2468
	Circumference 87"	88 1/2"		Circumference 87 1/4"	88 1/2"
	Air Pressure LF 22#	RF 44#		Air Pressure LF 28/43#	RF 56/71#
Outer/Inner	LR 22#	RR 40#	Outer/Inner	LR 29/44#	RR 54/69#
Daytona	LS	RS	Dover	LS	RS
	1485	2642		1013	2640
	Circumference 87 7/8"	88 1/2"		Circumference 87"	88 1/2"
	Air Pressure LF 35/50#	RF 55/70#		Air Pressure LF 26/41#	RF 52/67#
Outer/Inner	LR 35/50#	RR 50/65#	Outer/Inner	LR 26/41#	RR 50/65#
Iowa	LS	RS	Kansas	LS	RS
	1013	2262		1117	2468
	Circumference 87"	88 1/2"		Circumference 87 1/4"	88 1/2"
	Air Pressure LF 18#	RF 36#		Air Pressure LF 30/45#	RF 52/67#
Outer	LR 18#	RR 34#	Outer/Inner	LR 30/45#	RR 50/65#
Michigan	LS	RS	Phoenix	LS	RS
	1117	2468		1013	2262
	Circumference 87 1/4"	88 1/2"		Circumference 87"	88 1/2"
	Air Pressure LF 28/43#	RF 54/69#		Air Pressure LF 18#	RF 35#
Outer/Inner	LR 28/43#	RR 50/65#	Outer	LR 18#	RR 33#
Talladega	LS	RS			
	1485	2642			
	Circumference 87 7/8"	88 1/2"			
	Air Pressure LF 35/50#	RF 55/70#			
Outer/Inner	LR 35/50#	RR 50/65#			

Inner Liner cold inflation should be at least 15 PSI above the cold tire inflation.

Road Course 11.0/28R15 Radials	Road Course 12.0/28R15 Radials
Circumference-88 3/4"	Circumference-88 1/2"
Mid-Ohio	Watkins Glen
LF	LF 31#
RF	RF 29#
LR	LR 25#
RR	RR 25#

11.0/28R15 Radials
Circumference-Left Side 87 1/2" Right Side 88 3/4"

Berlin 27L/44R	LF 16#	RF 29#
	LR 16#	RR 29#
LOR 27L/44R	LF 18#	RF 32#
	LR 18#	RR 30#
Salem 27L/44R	LF 21#	RF 37#
	LR 21#	RR 35#

No Inner Liners Used

Elko 27L/44R	LF 16#	RF 32#
	LR 16#	RR 30#
Milwaukee 27L/44R	LF 18#	RF 30#
	LR 18#	RR 30#
Toledo 27L/44R	LF 18#	RF 33#
	LR 18#	RR 31#

Dirt Tracks (11.0/88-15) Bias Ply

DuQuoin 45L/70R Dirts	LF 18#	RF 24#
	LR 16#	RR 24#

Springfield 45L/70R Dirts	LF 18#	RF 22#
	LR 18#	RR 22#

- Nitrogen replacement procedure:**
- (1) Deflate outer chamber completely.
 - (2) Reduce inner chamber to **no less than 15#**
 - (3) Inflate inner to recommended pressure.
 - (4) Inflate outer to recommended pressure.

All Pressures are COLD Starting Recommended.
All Subject to Change.
Check with General Tire at each Event.

REV 1/3/24