

GENERAL TIRE

2025 ARCA TIRE SPECIFICATIONS

Speedway Codes (12.0/28.0R15)

Bristol	LS	RS	Charlotte	LS	RS
	1013	2262		1117	2468
	Circumference 87"	88 1/2"		Circumference 87 1/4"	88 1/2"
	Air Pressure LF 22#	RF 44/59#		Air Pressure LF 28/43#	RF 56/71#
Outer/Inner	LR 22#	RR 40/55#	Outer/Inner	LR 29/44#	RR 54/69#
Daytona	LS	RS	Iowa	LS	RS
	1485	2642		1013	2262
	Circumference 87 7/8"	88 1/2"		Circumference 87"	88 1/2"
	Air Pressure LF 35/50#	RF 55/70#		Air Pressure LF 18#	RF 36#
Outer/Inner	LR 35/50#	RR 50/65#	Outer	LR 18#	RR 34#
Kansas	LS	RS	Michigan	LS	RS
	1117	2468		1117	2468
	Circumference 87 1/4"	88 1/2"		Circumference 87 1/4"	88 1/2"
	Air Pressure LF 30/45#	RF 52/67#		Air Pressure LF 28/43#	RF 54/69#
Outer/Inner	LR 30/45#	RR 50/65#	Outer/Inner	LR 28/43#	RR 50/65#
Phoenix	LS	RS	Rockingham	LS	RS
	1013	2262		1013	2262
	Circumference 87"	88 1/2"		Circumference 87"	88 1/2"
	Air Pressure LF 18#	RF 35#		Air Pressure LF 23/38#	RF 47/62#
Outer	LR 18#	RR 33#	Outer/Inner	LR 23/38#	RR 47/62#
Talladega	LS	RS	Dover	LS	RS
	1485	2642		1013	2640
	Circumference 87 7/8"	88 1/2"		Circumference 87"	88 1/2"
	Air Pressure LF 35/50#	RF 55/70#		Air Pressure LF 26/41#	RF 52/67#
Outer/Inner	LR 35/50#	RR 50/65#	Outer/Inner	LR 26/41#	RR 50/65#

Inner Liner cold inflation should be at least 15 PSI above the cold tire inflation.

Road Course	11.0/28R15	Radials	Road Course	11.0/28R15	Radials
Circumference-88 3/4"			Circumference-88 3/4"		
Lime Rock	LF 28#	RF 28#	Watkins Glen	LF 32#	RF 30#
Tire Code 44	LR 24#	RR 24#	Tire Code 44	LR 26#	RR 26#

11.0/28R15 Radials			No Inner Liners Used		
Circumference-Left Side 87 1/2" Right Side 88 3/4"					
Berlin	LF 16#	RF 29#	Elko	LF 16#	RF 32#
27L/44R	LR 16#	RR 29#	27L/44R	LR 16#	RR 30#
LOR	LF 18#	RF 32#	Madison	LF 18#	RF 36#
27L/44R	LR 18#	RR 30#	27L/44R	LR 18#	RR 34#
Salem	LF 21#	RF 37#	Toledo	LF 18#	RF 33#
27L/44R	LR 21#	RR 35#	27L/44R	LR 18#	RR 31#

Dirt Tracks (11.0/88-15)	Bias Ply	Dirt Tracks	Bias Ply		
DuQuoin	LF 18#	RF 24#	Springfield	LF 18#	RF 22#
45L/70R Dirts	LR 16#	RR 24#	45L/70R Dirts	LR 18#	RR 22#

- Nitrogen replacement procedure:**
- (1) Deflate outer chamber completely.
 - (2) Reduce inner chamber to **no less than 15#**
 - (3) Inflate inner to recommended pressure.
 - (4) Inflate outer to recommended pressure.

5 Flags-Nashville and Flat Rock

All Pressures are COLD Starting Recommended.
All Subject to Change.
Check with General Tire at each Event.
REV 12/7/22

27's	44's
LF 16#	RF 32#
LR 16#	RR 30#